i-Vu CCN
Standard & Plus
Specifications

Carrier

Turn to the Experts.℠

The i-Vu CCN web appliance is an extremely powerful web server in a box. Packed full of standard features, it is available in two different versions. Refer to the feature comparison chart in this specification sheet to determine which version meets the requirements for your Carrier system.

Specifications

Power Requirements	110-220V AC ± 10%, 50-60 Hz
Operating Temperature	50ºF to 95ºF (10ºC to 35ºC). NOTE: For indoor use only.
Operating Humidity	0% to 95% RH, noncondensing
Storage Humidity	0% to 95% RH, noncondensing
Weight	3 lb. (1.49 kg)
Dimensions	<u>Overall</u> Width: 6-1/2" (165mm) Height: 1.97" (50mm) Depth: 6-1/2" (165mm)
Communication Ports	4 USB Ports 1 LAN port, RJ-45 10/100/1000Base-T Monitor and keyboard ports for troubleshooting purposes
Default Host Name	ivu
Listings	FC, UL, ULC, and CE
Compliance	RoHS

i-Vu CCN
Standard & Plus

Feature Comparison

Feature	Standard	Plus
Compact Web Appliance	√	√
Automatically Installs on customer's Ethernet	√	√
Internet Explorer and WAP device support	√	√
Auto-discovers CCN controllers and creates graphics	√	√
Dynamic comfort indicators on floorplans	√	√
Real-time, interactive equipment graphics	√	√
Web browser commissioning	√	√
Complete symbol library for creating customized graphics	√	√
Graphical scheduling and setpoint adjustment	√	√
Powerful alarm management	√	√
Advanced password policy and SSL for added security	√	√
Audit log, schedule, and equipment checkout reports	√	√
CCN connection	USB->CCN converter included	Requires Routers and/or Links
Supports i-Vu CCN Routers and i-Vu Links		√
Maximum CCN controllers supported	140	750 (140 per i-Vu CCN Router /Link)
Automatic historical trending	√ (7 days)	√ (2 months)
BACnet/Modbus/LonWorks integration with i-Vu Link		√
Tenant override billing reports		√
Equipment and trend value reports		√

Carrier ®

Turn to the Experts.™

www.carrier.com
1-800-CARRIER